

MACHINE SPECIFICATIONS



© Grizzly Industrial, Inc. • Phone #: (360) 647-0802 • Web: www.shopfoxtools.com

MODEL W1754H 20" PLANER WITH BUILT IN MOBILE BASE AND HELICAL CUTTERHEAD

Product Dimensions

| | |
|------------------------------------------------------------|------------------------------|
| Weight..... | 771 lbs. |
| Width (side-to-side) x Depth (front-to-back) x Height..... | 55-1/2 x 43-1/2 x 45-7/8 in. |
| Footprint (Length x Width)..... | 23-1/2 x 23-1/2 in. |

Shipping Dimensions

| | |
|------------------------------|------------------|
| Type..... | Wood Crate |
| Content..... | Machine |
| Weight..... | 924 lbs. |
| Length x Width x Height..... | 43 x 29 x 48 in. |

Electrical

| | |
|-------------------------------|---------------------------------------|
| Power Requirement..... | 240V, Single-Phase, 60 Hz |
| Full-Load Current Rating..... | 19A |
| Minimum Circuit Size..... | 30A |
| Connection Type..... | Cord & Plug |
| Power Cord Included..... | Yes |
| Power Cord Length..... | 6-1/2 ft. |
| Power Cord Gauge..... | 12 AWG |
| Plug Included..... | Yes |
| Included Plug Type..... | L6-30 |
| Switch Type..... | Magnetic Switch w/Overload Protection |

Motors

Main

| | |
|---------------------------------------|---------------------------------|
| Horsepower..... | 5 HP |
| Phase..... | Single-Phase |
| Amps..... | 19A |
| Speed..... | 3450 RPM |
| Type..... | TEFC Capacitor-Start Induction |
| Power Transfer | Triple V-Belt Drive |
| Bearings..... | Sealed & Permanently Lubricated |
| Centrifugal Switch/Contacts Type..... | External |

Main Specifications

Main Specifications

| | |
|-----------------------------------------------|------------|
| Max. Cut Width..... | 20 in. |
| Min. Stock Length..... | 8 in. |
| Min. Stock Thickness..... | 3/16 in. |
| Max. Stock Thickness..... | 8 in. |
| Number of Cuts Per Inch..... | 104, 83 |
| Number of Cuts Per Minute..... | 20,000 |
| Cutterhead Speed..... | 4800 RPM |
| Planing Feed Rate..... | 16, 20 FPM |
| Max. Cut Depth Planing Full Width..... | 1/8 in. |
| Max. Cut Depth Planing 6-Inch Wide Board..... | 1/8 in. |

Cutterhead Info

| | |
|-----------------------------------|-------------------|
| Cutterhead Type..... | Helical |
| Cutterhead Diameter | 3-1/8 in. |
| Number of Cutter Rows..... | 5 |
| Number of Indexable Cutters..... | 100 |
| Cutter Insert Type..... | Indexable Carbide |
| Cutter Insert Size Length..... | 15 mm |
| Cutter Insert Size Width..... | 15 mm |
| Cutter Insert Size Thickness..... | 2.5 mm |

Table Info

| | |
|---------------------------------------|---------------------|
| Table/Headstock Movement..... | 8 in. |
| Table Bed Size Length..... | 25-3/4 in. |
| Table Bed Size Width..... | 20 in. |
| Table Bed Size Thickness..... | 1-3/4 in. |
| Number of Bed Rollers..... | 2 |
| Floor-to-Table Height..... | 26-1/2 - 34-1/2 in. |
| Roller Ext. Table Size Length..... | 55-1/2 in. |
| Roller Ext. Table Size Width..... | 20 in. |
| Roller Ext. Table Size Thickness..... | 1-3/4 in. |

Construction

| | |
|--------------------------|----------------------------|
| Table..... | Precision-Ground Cast Iron |
| Body..... | Cast Iron |
| Stand..... | Steel |
| Cutterhead Assembly..... | Steel |
| Infeed Roller..... | Serrated Steel |
| Outfeed Roller..... | Knurled |
| Paint Type/Finish..... | Powder Coated |

Other

| | |
|----------------------------|---------------|
| Table/Headstock Locks..... | Yes |
| Measurement Scale..... | Inch & Metric |
| Number of Dust Ports..... | 1 |
| Dust Port Size..... | 5 in. |
| Mobile Base..... | Built-In |
| Gear Box..... | 2 Speed |

Other

| | |
|----------------------------------------------------------------------|---------------------------|
| Country of Origin | China |
| Warranty | 2 Years |
| Approximate Assembly & Setup Time | 30 Minutes |
| Serial Number Location | ID Label Top of Headstock |
| Sound Rating | 80 dB |
| ISO 9001 Factory | No |
| Certified by a Nationally Recognized Testing Laboratory (NRTL) | Yes |

Features

- Helical Cutterhead with German-Made Indexable Carbide Inserts
- Built-In Mobile Base
- Inch & Metric Measurement Scale
- Chip Breaker & Pressure Bar
- 0.059 in. Table Movement Distance per Handwheel Revolution
- Precision-Ground Cast-Iron Wings
- Top-Mounted Board Return Rollers
- Four Column Support with Positive Table Locks
- Two-Speed Automatic Board Feed
- Pedestal-Mounted Control Switch
- Two Adjustable Bed Rollers